EverprintPremiumWhite

Preprint & Offset

Description

The choicest recycled paper!

EverprintPremiumWhite is made from 100% recycled fibres without compromising on quality.
Raw materials are selected to offer the best whiteness, dimensional stability and outstanding printing quality in offset or preprint.
Its resolutely ecological production process greatly limits environmental impact by using biomass energy, by avoiding chlorinated fibre bleaching and by generating little waste.

With EverprintPremiumWhite you choose reliability with a recycled signature.

Technical specifications

Substance	*g*	**70**	**80**	**90**	**100**	**120**	**140**	**160**	**200**	**250**	**300**	**350**	**400**	*NF EN ISO 536*
Thickness	*µm*	88	100	113	125	150	168	192	240	288	345	403	460	*NF EN ISO 534*
Bulk	*cm^3/g*	1.25	1.25	1.25	1.25	1.25	1.20	1.20	1.20	1.15	1.15	1.15	1.15	*NF EN ISO 534*
Whiteness	*CIE*	145	145	145	145	145	145	145	145	145	145	145	145	*NF ISO 11475*
Brightness	*ISO*	100	100	100	100	100	100	100	100	100	100	100	100	*ISO 2470-2*
Bendtsen roughness	*ml/min*	230	230	230	230	230	230	230	230	230	230	230	230	*ISO 8791-2*
Absolute humidity	*%H_2O*	5	5	5	5	5	5,5	5,5	5,5	6	6	6	6	*NF EN ISO 20287*
Relative humidity	*% in the air*	40	40	40	40	40	45	45	45	48	48	48	48	*Sword measurement*
Opacity	*%*	90	95	95	96	97	97	98	>99	>99	>99	>99	>99	*NF ISO 2471*
Permanence		*DIN 6738 CL 24-85*												

These values are not contractual.
Revision date : 22/07/2019

Certifications

www.blauer-engel.de/uz14a

www.blauer-engel.de/uz56

UZ56 is used for all products >150gsm

The mark of responsible forestry

Please collect used paper for recycling

Version : EVB