

Rough Natural

Rebecca **Rock**

Description

The ultimate, natural medium Rough Natural is first and foremost a warm and subtle shade. Produced without bleaching agents (OBA), Rough Natural is an ideal substrate to guarantee a perfect chromatic balance. Its smooth surface, perfect sheet formation and high rigidity ensure an excellent processability. Your documents will be pleasant to read and hold. Rough Natural is compatible with offset, inkjet and laser printing techniques. Available from 80 to 400 gsm.

Technical specifications

Substance	gsm	80	90	100	120	130	150	170	200	240	300	350	400	NF EN ISO 536
Thickness	μm	106	122	132	157	170	194	219	258	307	375	440	504	NF EN ISO 534
Bulk	cm³/g	1.33	1.35	1.32	1.31	1.31	1.29	1.29	1.29	1.28	1.25	1.26	1.26	NF EN ISO 534
Whiteness	CIE ISO	————— indicative value 74 —————												NF ISO 11475 ISO 2470-2
Bendtsen roughness	ml/min	200	200	200	200	200	200	200	200	200	200	200	200	ISO 8791-2
Absolute humidity	%H ₂ O	4.6	4.6	5.0	5.5	5.5	5.5	5.5	6.0	6.0	6.5	6.5	6.5	NF EN ISO 20287
Relative humidity	% in the air	32	32	38	44	44	44	44	48	48	50	50	50	Sword measurement
Opacity	%	90	91	91	95	95	96	97	>98	>99	>99	>99	>99	NF ISO 2471

These values are not contractual.
Revision date: 24/02/2025

Certifications



ISO 9001 ✓
ISO 14001 ✓
ISO 50001 ✓