

Everprint Premium White

Life



30/10/2026

DESCRIPTION

Everprint Premium White is part of our recycled paper range. Specially designed for offset and preprint applications, this paper is made from 100% recovered fibres with no compromise on quality.

TECHNICAL SPECIFICATIONS

Specifications	Units													Standards
Substance	gsm	70	80	90	100	120	140	160	200	250	300	350	400	ISO 536
Thickness	µm	89	102	114	126	150	171	195	244	305	357	417	476	ISO 534
Bulk	cm³/g	1.27	1.27	1.27	1.26	1.25	1.22	1.22	1.22	1.22	1.19	1.19	1.19	
Stiffness	MD (mN.m)	0.3	0.3	0.3	0.6	1.0	1.6	2.1	4.2	6.3	12.4	18.7	21.0	ISO 2493 - 1
	CD (mN.m)	0.2	0.2	0.2	0.3	0.6	0.8	1.2	2.0	3.1	6.3	10.0	11.0	
Bendtsen roughness	ml/min	250	250	250	250	250	250	250	250	250	250	250	250	ISO 8791 - 2
Whiteness	CIE	135	135	135	135	135	135	135	135	135	135	135	135	ISO 11475
Brightness	ISO	97	97	97	97	97	97	97	97	97	100	100	100	ISO 2470 - 2
Absolute humidity	%H ₂ O	5.0	5.0	5.0	5.0	5.5	5.5	6.0	6.5	6.5	6.5	6.5	6.5	ISO 287
Relative humidity	% in the air	38	38	38	38	44	44	48	50	50	50	50	50	Sword measurement
Opacity	%	93	95	96	97	>99	>99	>99	>99	>99	>99	>99	>99	ISO 2471
Tensile strength	MD (daN/15mm)	5.0	5.6	6.5	6.6	7.7	7.8	8.9	10.4	12.9	19.3	19.3	22.8	ISO 1924 - 2
	CD (daN/15mm)	3.0	3.1	3.4	3.6	3.9	3.8	4.3	5.0	6.2	11.5	11.5	13.1	
Bursting strength	kPa.m²/g	2.0	2.1	2.1	2.0	2.0	1.8	1.8	1.6	1.6	2.3	2.3	2.3	ISO 2758
Tearing strength	mN	697	797	805	821	795	817	805	761	764	975	975	1082	ISO 1974
Elongation at break	MD (m)	1.7	1.9	2.0	1.9	1.9	2.0	2.0	1.9	1.7	2.6	2.6	2.3	ISO 1924 - 2
	CD (m)	4.0	5.4	5.4	5.4	5.0	4.9	4.6	4.3	4.0	7.0	7.0	6.4	



A symbol of Clairefontaine's innovation, the JetPro® logo guarantees high-performance papers specifically designed to deliver inkjet printing with optimal precision and color quality.

APPLICATIONS

Brochures	●
Cases	●
Box set	●
Illustrated books	●
Greeting cards	●

PRINTING SUGGESTIONS

Inkjet	●
Offset	●
Letterpress	●
Silk-screen	●
Hot foil stamping	●

CONVERTING SUGGESTIONS

Die-cutting	●
Embossing	●
Etching	●
Scoring	●
Folding	●
Glueing	●

*For packaging or book publishing, the fibres direction should run parallel to the main fold.

COMPLIANCE AND SUSTAINABILITY

No PFAS added

REACH (CE n° 1907/2006)
The product does not contain any candidate substances (SVHC)
listed by ECHA at a concentration exceeding 0.1% by mass.

CERTIFICATIONS



www.blauer-engel.de/uz14a



Please collect used paper for recycling



The mark of responsible forestry



ISO 9001
Quality Management System

ISO 14001
Environmental Management System

ISO 50001
Energy Management System