Eversatin Premium White

Life

30/10/2026

DESCRIPTION

Eversatin Premium White is a premium recycled paper, specially crafted for offset and preprint applications. Made entirely from 100% recovered fibres, it combines environmental responsibility with exceptional print quality.

TECHNICAL SPECIFICATIONS

Specifications	Units										Standards
Substance	gsm	**90**	**100**	**120**	**150**	**170**	**200**	**240**	**300**	**350**	ISO 536
Thickness	µm	96	107	128	160	182	220	264	330	385	ISO 534
Bulk	cm^3/g	1.07	1.07	1.07	1.07	1.07	1.10	1.10	1.10	1.10	
Stiffness	MD (mN.m)	0.3	0.6	1.0	1.6	2.1	4.2	6.3	12.4	18.7	ISO 2493 - 1
	CD (mN.m)	0.2	0.3	0.6	0.8	1.2	2.0	3.1	6.3	10.0	
Bekk Smoothness	s	70	70	70	70	70	70	70	70	70	ISO 8791 - 2
Whiteness	CIE	135	135	135	135	135	135	135	135	135	ISO 11475
Brightness	ISO	100	100	100	100	100	100	100	100	100	ISO 2470 - 2
Absolute humidity	$\%H_2O$	5.0	5.0	5.5	5.5	5.5	6.0	6.5	6.5	6.5	ISO 287
Relative humidity	% in the air	40	40	45	45	45	50	56	56	56	Sword measurement
Opacity	%	96	97	98	99	>99	>99	>99	>99	>99	ISO 2471
Tensile strength	MD (daN/15mm)	6.5	6.6	7.4	7.8	8.9	10.4	12.9	19.3	19.3	ISO 1924 - 2
	CD (daN/15mm)	3.4	3.6	5.0	3.8	4.3	5.0	6.2	11.5	11.5	
Bursting strength	$kPa.m^2/g$	2.1	2.0	2.3	1.8	1.8	1.6	1.6	2.3	2.3	ISO 2758
Tearing strength	mN	805	821	795	817	805	761	764	975	1082	ISO 1974
Elongation at break	MD (m)	2.0	1.9	2.4	2.0	2.0	1.9	1.7	2.6	2.6	ISO 1924 - 2
	CD (m)	5.4	5.4	6.2	4.9	4.6	4.3	4.0	7.0	7.0	

JetPro™ TECHNOLOGY

A symbol of Clairefontaine's innovation, the JetPro® logo guarantees high-performance papers specifically designed to deliver inkjet printing with optimal precision and color quality.

APPLICATIONS

Brochures	●
Cases	●
Box set	●
Illustrated books	●
Greeting cards	●

PRINTING SUGGESTIONS

Inkjet	●
Offset	●
Letterpress	●
Silk-screen	●
Hot foil stamping	●

CONVERTING SUGGESTIONS

Die-cutting	●
Embossing	●
Etching	●
Scoring	●
Folding	●
Glueing	●

*For packaging or book publishing, the fibres direction should run parallel to the main fold.

COMPLIANCE AND SUSTAINABILITY

No PFAS added

REACH (CE n° 1907/2006)
The product does not contain any candidate substances (SVHC) listed by ECHA at a concentration exceeding 0.1% by mass.

CERTIFICATIONS

www.blauer-engel.de/uz14a

FSC www.fsc.org FSC® C002321 The mark of responsible forestry

ECF ELEMENTAL Chlorine FREE

ISO 9001
Quality Management System

ISO 14001
Environmental Management System

ISO 50001
Energy Management System