

DCP Green

Impression Couleur Laser

Description

DCP quality in 100% recycled fibres.

Its high whiteness and perfectly smooth surface of DCP Green promote a high quality reproduction. Its high opacity guarantees double-sided printing.

Recommended for copiers, laser printers and inkjet systems.

Plain paper setting for inkjet printing.

Applications

External communication. All documents containing text and colors. Reproduction of images.

Technical specifications

| Substance | gsm | 90 | 100 | 120 | 160 | 200 | 250 | NF EN ISO 536 |
|-----------------|-------|------|------|------|-------------------|------|------|---------------|
| Thickness | µm | 91 | 101 | 121 | 163 | 204 | 255 | NF EN ISO 534 |
| Bulk | cm³/g | 1.01 | 1.01 | 1.01 | 1.02 | 1.02 | 1.02 | NF EN ISO 534 |
| Whiteness | CIE | 135 | 135 | 135 | 135 | 135 | 135 | NF ISO 11475 |
| | ISO | 97 | 97 | 97 | 97 | 97 | 97 | ISO 2470-2 |
| Bekk smoothness | s | 220 | 220 | 220 | 220 | 220 | 220 | NF ISO 5627 |
| Opacity | % | 96 | 96 | 98 | >99 | >99 | >99 | NF ISO 2471 |
| Permanence | | | | | DIN 6738 CL 24-85 | | | |

These values are not contractual.

Revision date: 2024/07/22

Certifications



www.blauer-engel.de/uz14a



EU Ecolabel
www.ecolabel.eu
EU Ecolabel - FR/01/006
Please collect used paper for recycling



FSC
www.fsc.org
FSC C002321
The mark of responsible forestry



ISO 9001 ✓

ISO 14001 ✓

ISO 50001 ✓